6" height

FS OR-G-AT7

FS OR-G-AT8

25.75" width | 38.125" width | 47.75" width | 47.75" width | 38.125" width | 25.75" width

Antares
10' x 20' Truss System
Dye Sub Printed

TEMPLATE IS @ 1/2 SCALE
Panels AT-1 and AT-6:
Total Graphic Area: 29.75" w x 87.75"h
Finished Size: 25.75"w x 83.75"h

Panels AT-2 and AT-5:
Total Graphic Area: 42.125"w x 87.75"h
Finished Size: 38.125"w x 83.75"h

Panels AT-3 and AT-4:
Total Graphic Area: 51.75"w x 87.75"h
Finished Size: 47.75"w x 83.75"h

Panels AT-7 and AT-8:
Total Graphic Area: 86.5"w x 10"h
Finished Size: 82.5"w x 6"h

Template requires 1" bleed around the perimeter (2" around the perimeter when scaled to 200% and printed)

FS = Graphic is front side mounted (3/4" w velcro is applied to the back of the panel)
BS = Graphic is back side mounted (3/4"w velcro is applied to the front of the panel)
Notching = 7/8" square that is cut into the appropriate location.
Hinging= 3/4" strip of material that is created by notching the graphic. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

- CMYK Color Mode
- All Solid Coated Pantone colors should be called out in the art as spot colors
- Embed all images and support files
- Resolution must be 200-240 ppi @ 1/2 size, 100-120ppi @ 100% size
- All fonts must be created to outlines
- Do not scale artboard
- Background color/images must bleed to the edge of artboard
- Do not use spot colors from template in your artwork as they will not print

BS
OR-G-AT1

bleed area
trim line

BS
OR-G-AT2

BS
OR-G-AT3

BS
OR-G-AT4

BS
OR-G-AT5

BS
OR-G-AT6

gray area will be obstructed once finished and mounted

Antares
10′ x 20′ Truss System
Dye Sub Printed



TEMPLATE IS @ 1/2 SCALE
Panels AT-1 and AT-6:
Total Graphic Area: 29.75″ w x 87.75″h
Finished Size: 25.75″w x 83.75″h

Panels AT-2 and AT-5:
Total Graphic Area: 42.125″w x 87.75″h
Finished Size: 38.125″w x 83.75″h

Panels AT-3 and AT-4:
Total Graphic Area: 51.75″w x 87.75″h
Finished Size: 47.75″w x 83.75″h

Panels AT-7 and AT-8:
Total Graphic Area: 86.5″w x 10″h
Finished Size: 82.5″w x 6″h

Template requires 1″ bleed around the perimeter (2″ around the perimeter when scaled to 200% and printed)

FS = Graphic is front side mounted (3/4″ w velcro is applied to the back of the panel)
BS = Graphic is back side mounted (3/4″w velcro is applied to the front of the panel)
Notching = 7/8″ square that is cut into the appropriate location.
Hinging= 3/4″ strip of material that is created by notching the graphic. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

- CMYK Color Mode
- All Solid Coated Pantone colors should be called out in the art as spot colors
- Embed all images and support files
- Resolution must be 200-240 ppi @ 1/2 size, 100-120ppi @ 100% size
- All fonts must be created to outlines
- Do not scale artboard
- Background color/images must bleed to the edge of artboard
- Do not use spot colors from template in your artwork as they will not print

BS

OR-G-AT1

bleed area
trim line

BS

OR-G-AT2

BS

OR-G-AT3

BS

OR-G-AT4

BS

OR-G-AT5

BS

OR-G-AT6

gray area will
be obstructed
once finished
and mounted

FS OR-G-AT7

FS OR-G-AT8