6" height

FS OR-G-AT7

FS OR-G-AT8

25.75" width | 38.125" width | 47.75" width | 47.75" width | 38.125" width | 25.75" width

Antares
10' x 20' Truss System
UV Printed

TEMPLATE IS @ 1/2 SCALE
Panels AT-1 and AT-6:
Total Graphic Area: 26.75" w x 84.75"h
Finished Size: 25.75"w x 83.75"h

Panels AT-2 and AT-5:
Total Graphic Area: 39.125"w x 84.75"h
Finished Size: 38.125"w x 83.75"h

Panels AT-3 and AT-4:
Total Graphic Area: 48.75"w x 84.75"h
Finished Size: 47.75"w x 83.75"h

Panels AT-7 and AT-8:
Total Graphic Area: 83.5"w x 7"h
Finished Size: 82.5"w x 6"h

Template requires 1/4" bleed around the perimeter (1/2" around the perimeter when scaled to 200% and printed)

FS = Graphic is front side mounted (3/4" w magnet is applied to the back of the panel)
BS = Graphic is back side mounted (3/4" w velcro is applied to the front of the panel)
Notching = 7/8" square that is cut into the appropriate location.
Hinging= 3/4" strip of material that is cropped from the panel and reapplied with hinge tape. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

- CMYK Color Mode
- All Solid Coated Pantone colors should be called out in the art as spot colors
- Embed all images and support files
- Resolution must be 200-240 ppi @ 1/2 size, 100-120ppi @ 100% size
- All fonts must be created to outlines
- Do not scale artboard
- Background color/images must bleed to the edge of artboard
- Do not use spot colors from template in your artwork as they will not print

BS
OR-G-AT1

BS
OR-G-AT2

BS
OR-G-AT3

BS
OR-G-AT4

BS
OR-G-AT5

BS
OR-G-AT6

gray area will be obstructed once finished and mounted

bleed area
trim line

Antares
10’ x 20’ Truss System
UV Printed



TEMPLATE IS @ 1/2 SCALE
Panels AT-1 and AT-6:
Total Graphic Area: 26.75” w x 84.75”h
Finished Size: 25.75”w x 83.75”h

Panels AT-2 and AT-5:
Total Graphic Area: 39.125”w x 84.75”h
Finished Size: 38.125”w x 83.75”h

Panels AT-3 and AT-4:
Total Graphic Area: 48.75”w x 84.75”h
Finished Size: 47.75”w x 83.75”h

Panels AT-7 and AT-8:
Total Graphic Area: 83.5“w x 7”h
Finished Size: 82.5“w x 6”h

Template requires 1/4” bleed around the perimeter (1/2” around the perimeter when scaled to 200% and printed)

FS = Graphic is front side mounted (3/4“ w magnet is applied to the back of the panel)
BS = Graphic is back side mounted (3/4“ w velcro is applied to the front of the panel)
Notching = 7/8” square that is cut into the appropriate location.
Hinging= 3/4” strip of material that is cropped from the panel and reapplied with hinge tape. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

– CMYK Color Mode
– All Solid Coated Pantone colors should be called out in the art as spot colors
– Embed all images and support files
– Resolution must be 200-240 ppi @ 1/2 size, 100-120ppi @ 100% size
– All fonts must be created to outlines
– Do not scale artboard
– Background color/images must bleed to the edge of artboard
– Do not use spot colors from template in your artwork as they will not print

BS

OR-G-AT1

— bleed area
— trim line

BS

OR-G-AT2

BS

OR-G-AT3

BS

OR-G-AT4

BS

OR-G-AT5

BS

OR-G-AT6

gray area will
be obstructed
once finished
and mounted

FS OR-G-AT7

FS OR-G-AT8