FS OR-G-CO3

47.75" width

83.75" height

BS

OR-G-CO1

bleed area
trim line

FS OR-G-CO4

47.75" width

Clio
10' x 10' Truss System
UV Printed



Panels CO1 and CO2:
Total Graphic Area: 48.75"w x 84.75"h
Finished Size: 47.75"w x 83.75"h
Visual Size: 45.75"w x 81.75"h

Panels CO3 and CO4:
Total Graphic Area: 83.5"w x 7"h
Finished Size: 82.5"w x 6"h
Visual Size: 82.5"w x 6"h

Template requires 1/2" bleed around the perimeter

FS = Graphic is front side mounted (3/4" w magnet is applied to the back of the panel)
BS = Graphic is back side mounted (3/4" w velcro is applied to the front of the panel)
Notching = 7/8" square that is cut into the appropriate location.
Hinging= 3/4" strip of material that is cropped from the panel and reapplied with hinge tape. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

- CMYK Color Mode
- All Solid Coated Pantone colors should be called out in the art as spot colors
- Embed all images and support files
- Resolution must be 100-120ppi
- All fonts must be created to outlines
- Do not scale artboard
- Background color/images must bleed to the edge of artboard
- Do not use spot colors from template in your artwork as they will not print

BS

OR-G-CO2

gray area will be obstructed once finished and mounted

BS

OR-G-CO1

bleed area

trim line

Clio
10’ x 10’ Truss System
UV Printed



Panels CO1 and CO2:
Total Graphic Area: 48.75”w x 84.75”h
Finished Size: 47.75”w x 83.75”h
Visual Size: 45.75”w x 81.75”h

Panels CO3 and CO4:
Total Graphic Area: 83.5”w x 7”h
Finished Size: 82.5”w x 6”h
Visual Size: 82.5”w x 6”h

Template requires 1/2” bleed around
the perimeter

FS = Graphic is front side mounted
(3/4“ w magnet is applied to the back
of the panel)
BS = Graphic is back side mounted
(3/4“ w velcro is applied to the front
of the panel)
Notching = 7/8” square that is cut into the
appropriate location.
Hinging= 3/4” strip of material that is cropped
from the panel and reapplied with hinge tape.
Allows two graphics to share the same
extrusion corner.

General Art Guidelines:

– CMYK Color Mode
– All Solid Coated Pantone colors should
be called out in the art as spot colors
– Embed all images and support files
– Resolution must be 100-120ppi
– All fonts must be created to outlines
– Do not scale artboard
– Background color/images must
bleed to the edge of artboard
– Do not use spot colors from template
in your artwork as they will not print

BS
OR-G-CO2

gray area will
be obstructed
once finished
and mounted

FS OR-G-CO3

FS OR-G-CO4