Hybrid Pro Modular Kit:
Hybrid Pro Modular Kit 10

TEMPLATE @ 1/2 SIZE

Dye Sub Graphic Panel A and F
Total Graphic Area: 95.4375"w x 98.375"h
Finished Graphic Area: 91.4375"w x 94.4375"h

Dye Sub Graphic Panel B and E
Total Graphic Area: 15.6875 x 98.375"h
Finished Graphic Area: 11.6875"w x 94.375"h

Dye Sub Graphic Panel C and D
Total Graphic Area: 73.0625"w x 98.375"h
Finished Graphic Area: 69.0625"w x 94.375"h

UV Graphic Panel G (Cabinet Door)
Total Graphic Area: 32.625"w x 32.75"h
Finished Graphic Area: 31.625"w x 31.75"h

Please be sure to include a 2" bleed around the perimeter of panel A, B, C, D, E and F.

Please be sure to include a .5" bleed around the perimeter of panel G.

Please consider obstructions and spaces created by the extrusions when designing your graphics.

General Art Guidelines:

- CMYK Color Mode
- All Solid Coated Pantone colors should be called out in the art as spot colors
- Embed all images and support files
- Resolution must be 200-240 ppi at 1/2 size, 100-120 ppi at full size
- All fonts must be created to outlines
- Do not scale artboard
- Background colorimages must bleed to the edge of artboard
- Do not use spot colors from template in your artwork as they will not print



Hybrid Pro Modular Kit:
Hybrid Pro Modular Kit 10



TEMPLATE @ 1/2 SIZE

Dye Sub Graphic Panel A and F
Total Graphic Area: 95.4375”w x 98.375”h
Finished Graphic Area: 91.4375”w x 94.4375”h

Dye Sub Graphic Panel B and E
Total Graphic Area: 15.6875 x 98.375”h
Finished Graphic Area: 11.6875”w x 94.375”h

Dye Sub Graphic Panel C and D
Total Graphic Area: 73.0625”w x 98.375”h
Finished Graphic Area: 69.0625”w x 94.375”h

UV Graphic Panel G (Cabinet Door)
Total Graphic Area: 32.625”w x 32.75”h
Finished Graphic Area: 31.625”w x 31.75”h

Please be sure to include a 2” bleed
around the perimeter of panel A, B, C, D, E and F.

Please be sure to include a .5” bleed
around the perimeter of panel G.

Please consider obstructions and spaces
created by the extrusions when designing
your graphics.

General Art Guidelines:

- CMYK Color Mode
- All Solid Coated Pantone colors should be called out in the art as spot colors
- Embed all images and support files
- Resolution must be 200-240 ppi at 1/2 size, 100-120 ppi at full size
- All fonts must be created to outlines
- Do not scale artboard
- Background color/images must bleed to the edge of artboard
- Do not use spot colors from template in your artwork as they will not print

PANEL A

Literatu
Rack
Obstruc

PANEL B

ure
k
tion

PANEL C

Cabinet 0
see below f
(door of cabin

Literature
Review
Obstruction
for template
(sheet faces front)

PANEL D

erature
Rack
truction

PANEL E

PANEL F

bleed area
trim line
safe area

PANEL G
Cabinet Graphic