Metis
10′ x 10′ Truss System
UV Printed

TEMPLATE IS @ 1/2 SCALE
Panels MT1 and MT5:
Total Graphic Area: 44″w x 38.75″h
Finished Size: 43″w x 37.75″h
Visual Size: 41″w x 35.75″h

Panels MT2, MT3 and MT4:
Total Graphic Area: 44″w x 91″h
Finished Size: 43″w x 90″h
Finished Size: 41″w x 88″h

Template requires 1/4″ bleed around the perimeter (1/2″ around the perimeter when scaled to 200% and printed)

FS = Graphic is front side mounted (3/4″ w magnet is applied to the back of the panel)
BS = Graphic is back side mounted (3/4″ w velcro is applied to the front of the panel)
Notching = 7/8″ square that is cut into the appropriate location.
Hinging= 3/4″ strip of material that is cropped from the panel and reapplied with hinge tape. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

– CMYK Color Mode
– All Solid Coated Pantone colors should be called out in the art as spot colors
– Embed all images and support files
– Resolution must be 200-240 ppi @ 1/2 size, 100-120ppi @ 100% size
– All fonts must be created to outlines
– Do not scale artboard
– Background color/images must bleed to the edge of artboard
– Do not use spot colors from template in your artwork as they will not print

90″ height

43″ width

BS
OR-G-MT1

bleed area
trim line

BS
OR-G-MT2

BS
OR-G-MT3

BS
OR-G-MT4

43″ width

BS
OR-G-MT5

gray area will be obstructed once finished and mounted

BS

OR-G-MT1

bleed area

trim line

Metis
10′ x 10′ Truss System
UV Printed



TEMPLATE IS @ 1/2 SCALE
Panels MT1 and MT5:
Total Graphic Area: 44″w x 38.75″h
Finished Size: 43″w x 37.75″h
Visual Size: 41″w x 35.75″h

Panels MT2, MT3 and MT4:
Total Graphic Area: 44″w x 91″h
Finished Size: 43″w x 90″h
Finished Size: 41″w x 88″h

Template requires 1/4″ bleed around the perimeter (1/2″ around the perimeter when scaled to 200% and printed)

FS = Graphic is front side mounted (3/4″ w magnet is applied to the back of the panel)
BS = Graphic is back side mounted (3/4″ w velcro is applied to the front of the panel)
Notching = 7/8″ square that is cut into the appropriate location.
Hinging= 3/4″ strip of material that is cropped from the panel and reapplied with hinge tape. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

– CMYK Color Mode
– All Solid Coated Pantone colors should be called out in the art as spot colors
– Embed all images and support files
– Resolution must be 200-240 ppi @ 1/2 size, 100-120ppi @ 100% size
– All fonts must be created to outlines
– Do not scale artboard
– Background color/images must bleed to the edge of artboard
– Do not use spot colors from template in your artwork as they will not print

BS

OR-G-MT2

BS

OR-G-MT3

BS

OR-G-MT4

BS

OR-G-MT5

gray area will
be obstructed
once finished
and mounted