Omicron
10' x 20' Truss System
UV Printed

TEMPLATE IS @ 1/2 SCALE
Panels OM1, OM3, OM5, and OM7:
Total Graphic Area: 39.125"w x 84.75"h
Finished Size: 38.125"w x 83.75"h

Panel OM2 and OM6:
Total Graphic Area: 38.75"w x 84.75"h
Finished Size: 37.75"w x 83.75"h

Panel OM4:
Total Graphic Area: 48.75"w x 84.75"h
Finished Size: 47.75"w x 83.75"h

Template requires 1/4" bleed around the perimeter (1/2" around the perimeter when scaled to 200% and printed)

FS = Graphic is front side mounted (3/4" w magnet is applied to the back of the panel)
BS = Graphic is back side mounted (3/4" w velcro is applied to the front of the panel)
Notching = 7/8" square that is cut into the appropriate location.
Hinging= 3/4" strip of material that is cropped from the panel and reapplied with hinge tape. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

- CMYK Color Mode
- All Solid Coated Pantone colors should be called out in the art as spot colors
- Embed all images and support files
- Resolution must be 200-240 ppi @ 1/2 size, 100-120ppi @ 100% size
- All fonts must be created to outlines
- Do not scale artboard
- Background color/images must bleed to the edge of artboard
- Do not use spot colors from template in your artwork as they will not print

BS
OR-G-OM1

panel is hinged
on right side

BS
OR-G-OM2

panel is notched
on top and bottom
left side

BS
OR-G-OM3

BS
OR-G-OM4

BS
OR-G-OM5

BS
OR-G-OM6

panel is notched
on top and bottom
right side

BS
OR-G-OM7

panel is hinged
on left side

— bleed area
— trim line

gray area will
be obstructed
once finished
and mounted

Omicron
10′ x 20′ Truss System
UV Printed



TEMPLATE IS @ 1/2 SCALE
Panels OM1, OM3, OM5, and OM7:
Total Graphic Area: 39.125″w x 84.75″h
Finished Size: 38.125″w x 83.75″h

Panel OM2 and OM6:
Total Graphic Area: 38.75″w x 84.75″h
Finished Size: 37.75″w x 83.75″h

Panel OM4:
Total Graphic Area: 48.75″w x 84.75″h
Finished Size: 47.75″w x 83.75″h

Template requires 1/4″ bleed around the perimeter (1/2″ around the perimeter when scaled to 200% and printed)

FS = Graphic is front side mounted (3/4″ w magnet is applied to the back of the panel)
BS = Graphic is back side mounted (3/4″ w velcro is applied to the front of the panel)
Notching = 7/8″ square that is cut into the appropriate location.
Hinging= 3/4″ strip of material that is cropped from the panel and reapplied with hinge tape. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

- CMYK Color Mode
- All Solid Coated Pantone colors should be called out in the art as spot colors
- Embed all images and support files
- Resolution must be 200-240 ppi @ 1/2 size, 100-120ppi @ 100% size
- All fonts must be created to outlines
- Do not scale artboard
- Background color/images must bleed to the edge of artboard
- Do not use spot colors from template in your artwork as they will not print

BS

OR-G-OM1

panel is hinged on right side

— bleed area
— trim line

BS

OR-G-OM2

panel is notched
on top and bottom
left side

BS

OR-G-OM3

BS

OR-G-OM4

BS

OR-G-OM5

BS

OR-G-OM6

panel is notched
on top and bottom
right side

BS

OR-G-OM7

panel is hinged
on left side

gray area will
be obstructed
once finished
and mounted