BS
OR-G-VS1

BS
OR-G-VS3

BS
OR-G-VS5

BS
OR-G-VS7

Vesta
20′ x 20′ Truss System
Dye Sub Printed

Panels VS1, VS3, VS5 and VS7:
Total Graphic Area: 43.5″w x 41.75″h
Finished Size: 39.5″w x 37.75″h
Visual Size: 37.5″w x 35.75″h

Panels VS2, ZS4, ZS6 and ZS8:
Total Graphic Area: 43.5″w x 87.75″h
Finished Size: 39.5″w x 83.75″h
Visual Size: 37.5″w x 81.75″h

Template requires 2″ bleed around the perimeter

FS = Graphic is front side mounted (3/4″ w velcro is applied to the back of the panel)
BS = Graphic is back side mounted (3/4″w velcro is applied to the front of the panel)
Notching = 7/8″ square that is cut into the appropriate location.
Hinging= 3/4″ strip of material that is created by notching the graphic. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

- CMYK Color Mode
- All Solid Coated Pantone colors should be called out in the art as spot colors
- Embed all images and support files
- Resolution must be 100-120ppi
- All fonts must be created to outlines
- Do not scale artboard
- Background color/images must bleed to the edge of artboard
- Do not use spot colors from template in your artwork as they will not print

BS
OR-G-VS2

bleed area
trim line

BS
OR-G-VS4

BS
OR-G-VS6

BS
OR-G-VS8

gray area will be obstructed once finished and mounted

BS
OR-G-VS1

BS
OR-G-VS3

Vesta
20’ x 20’ Truss System
Dye Sub Printed





Panels VS1, VS3, VS5 and VS7:
Total Graphic Area: 43.5”w x 41.75”h
Finished Size: 39.5”w x 37.75”h
Visual Size: 37.5”w x 35.75”h

Panels VS2, ZS4, ZS6 and ZS8:
Total Graphic Area: 43.5”w x 87.75”h
Finished Size: 39.5”w x 83.75”h
Visual Size: 37.5”w x 81.75”h

Template requires 2” bleed around the perimeter

FS = Graphic is front side mounted (3/4” w velcro is applied to the back of the panel)
BS = Graphic is back side mounted (3/4”w velcro is applied to the front of the panel)
Notching = 7/8” square that is cut into the appropriate location.
Hinging= 3/4” strip of material that is created by notching the graphic. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

- CMYK Color Mode
- All Solid Coated Pantone colors should be called out in the art as spot colors
- Embed all images and support files
- Resolution must be 100-120ppi
- All fonts must be created to outlines
- Do not scale artboard
- Background color/images must bleed to the edge of artboard
- Do not use spot colors from template in your artwork as they will not print

BS

OR-G-VS2

bleed area
trim line

BS

OR-G-VS3

BS

OR-G-VS4

BS

OR-G-VS5

BS

OR-G-VS6

BS

OR-G-VS7

BS

OR-G-VS8

gray area will
be obstructed
once finished
and mounted